

ΑΛΕΞΑΝΔΡΟΣ ΚΑΛΟΓΙΑΝΝΗΣ & ΣΙΑ Ε.Ε.

ΕΙΣΑΓΩΓΕΣ // ΑΝΤΙΠΡΟΣΩΠΕΙΕΣ // ΕΜΠΟΡΙΑ
ΓΡΑΦΙΚΗ ΥΛΗ // ΥΛΙΚΑ ΣΥΣΚΕΥΑΣΙΑΣ // ΚΟΛΛΕΣ

Φράγκων 16, 54626 Θεσσαλονίκη

T: 2310 55.55.57 // 2310 526.066 // 2310 528.322

E: info@kalogiannis.gr // [kalogiannis.gr](mailto:info@kalogiannis.gr)

A.Φ.Μ. 093309400 Δ.Ο.Υ. Ε΄ Θεσσαλονίκης ΑΡ. ΓΕΜΗ: 57339304000



ΚΑΛΟΓΙΑΝΝΗΣ

— EST 1970 —

TECHNICAL SPECIFICATIONS **OPP LOW NOISY TAPE**

COMPOSITION

BACKING: Polypropylene film

ADHESIVE: Water based acrylic polymers dispersion

CORE: paper

AVAILABLE COLORS : Brown – transparent

BACKING THICKNESS: 28MY

TOTAL THICKNESS :50MY

ADHESIVE THICKNESS : 22MY

ADHESION TO STEEL (N/25mm) =/ > 5.0

ROLLING BACK (mm): =/>14.0 (10mm)

HOLDING POWER TO STEEL(hour) =/ 18

It is good practice to use the product within 12 months from purchase date (6 months if jumbo roll). The rolls must be kept in their original packing. Keep the product out of the light and protect from direct heat sources. The tape must be kept in a dry place, at humidity level below 65%, preferably at a temperature between 15° C and 25° C. If the storage temperature is different, restore the tape back to above level before using it. The values in the informative data sheets are the average results of tests made on our standard production and are not legally binding. The aesthetic and technical features may be subject to some changes caused by ageing, even though the quality level of the product is maintained. Nast shall not be liable for direct damages or for any consequence arising from the misuse of the product. We suggest the verification of the product suitability to the specific condition of use.

All above information are according to our raw material supplier's technical data sheet jumbo roll .