

Technical Data Sheet

Rust-Oleum Magnetic Chalkboard Paint (Brush 750ml & 2.5L)
Black Matt Finish

Create a magnetic chalkboard, perfect for walls, wood, metal and more. Works with conventional chalks and liquid chalk markers. Quick-drying formulation.

Interior Use

Ideal for use on wood, metal, plastic, paper and most other surfaces - please test on a small area first to check adhesion and compatibility.

Directions: Stir well before use. Use only when temperature is between 10-32°C and humidity is below 85% to ensure proper drying.

Preparation: Previously painted surfaces should be lightly abraded to provide a key. Bare metal and wood should be suitably primed prior to painting.

Application: Apply paint with a soft brush using light, even strokes taking care to avoid unsightly runs. A minimum of 3 coats are recommended, to be applied at a coverage rate of 5m²/L/coat. Best results are achieved with strong, light magnets.

Drying: Dries to touch in 30-60 minutes.

Recoating: Allow at least 2 hours between coats. Allow a minimum of 24 hours before applying chalk.

Cleaning: Clean brushes immediately after use with White Spirit.

Shelf Life: 2 years (unopened) from date of manufacture. (See base of can).

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements. Drying times are based on warm (15°C), dry applications conditions with good ventilation. Lower temperatures and higher humidity will prolong drying times. EU Limit value for this product (Cat A/i):500g/l. This Product contains a maximum of 375g/l VOC.

Tor Coatings Limited, Portobello Industrial Estate, Birtley, Chester-le-Street, Co. Durham, DH3 2RE, UK.

Technical Services Department: 0191 410 6611

E-mail: info@tor-coatings.com www.tor-coatings.com or www.rustoleumspraypaint.com

03/02/2016